



PAINT LOCKER + SUPPRESSION SYSTEM

- 3 level aluminum shelving and containment floor for hazardous spills.
- Organize paint & flammable storage on offshore platforms safely and efficiently.
- Minimize waste & improve longevity of unused paint.
- Additional 40 sq. ft. of containment floor space for added storage.

DNV/ISO CORNER CASTING

- Stackable container allows for any intermodal means of transportation
- Handling options include forklift or crane with sling
- DNV certified IWRC wire rope lifting sling equipped with Crosby safety pin bow shackles
- Uniquely numbered, tagged and certified

EXTERNAL DIMENSIONS

- Width: 1,828 mm (6')
- Length: 1,828 mm (6')
- Height: 2,438 mm (8')

RATINGS

- Max Gross : 5,400 kg (11,905 lbs)
- Payload: 4,000 kg (8,820 lbs)
- Tare (+/- 2%): 1,339 kg (3,085 lbs)

INTERNAL DIMENSIONS

- Width: 1,612.9 mm (5' 3.5")
- Length: 1,625.6 mm (5'4")
- Height: 2,095.5 mm (6' 10.5")

FLOOR AREA

• Floor area loading: 413 psf.





1417 Hugh Wallis Road S. Lafayette, La 70508 Office: 337-886-6631 Fax: 337-886-6633 www.TrinityRentalServices.com